

XADO Atomic Oil 10W-40 4T MA Super Synthetic



XADO ATOMIC OIL 10W-40 4T MA Super Synthetic Full synthetic oil for 4-stroke engines of motor equipment.

Contains atomic revitalizant. Specially colored green. Applied for 4-stroke engines of motorcycles, scooters, all-terrain vehicles and other motor equipment.

Specially recommended for engines operating under heavy loads.

Description:

- ❖ XADO Atomic Oil 10W-40 4T MA Super Synthetic is a full synthetic oil of the latest generation with viscosity SAE 10W-40 for 4-stroke engines of motor equipment. Meets and exceeds the highest requirements for the oils for 4-stroke engines of motorcycles (JASO MA).
- ❖ Base oil for XADO Atomic 10W-40 4T MA is made on the basis of complex synthetic base oils from the North Sea oil. Alloyed with special additive package.
- ❖ High reliability and stability to extreme loads will be always kept in top condition due to the patented formula of atomic revitalizant, included into XADO Atomic Oil. Application of revitalizants is considered as a prospective direction in the area of energy and resource-savings and is confirmed by certification tests in 35 countries of the world.
- ❖ specially designed for modern high-power 4-stroke engines of motorcycles, operating under heavy loads (high speed, long-term maximum and/or dynamic loads);
- ❖ very effective for engines of road and off-road motorcycles with integrated (or separated) transmission;
- ❖ ensures smooth gear shift and provides reliable clutch operation in the oil bath;
- ❖ owing to improved detergent properties, the oil keeps the engine completely clean;

Performance level:

XADO Atomic Oil 10W-40 4T MA Super Synthetic meets the requirements for the following specifications

SAE 10W-40

JASO MA/MA2

API SL

Application:

When using the oil, please consider recommendations of the manufacturer of the correspondent equipment.

XADO SMART NANOTECHNOLOGY FOR YOUR CAR

XADO Lube B.V. Energiestraat 12 7442 DA, Postbus 135 7440 AC, Nijverdal, Nederland
 Tel: 0548-615165 Fax 0548-610195 www.eurol.com info@eurol.com

Typical values:

Density at 20 °C, kg/l	0,872
Viscosity at 100 °C, mm ² /s	15,0
Viscosity at 40 °C, mm ² /s	100,5
Viscosity index	156
Flash point, °C	>200
Pour point, °C	<-32
Base number, mgKOH/g	>8,5
Sulfated ash, wt.	>1,0
Color, visual	green

Package:

Art. XA 20132 (Can 1 L)
 Art. XA 28532 (Can 20 L)
 Art. XA 20632 (Barrel 60 L)
 Art. XA 20732 (Barrel 200 L)