

**XADO**

SMART NANOTECHNOLOGY FOR YOUR CAR

XADO Technology Ltd. Headquarters: 4, 23 Augusta Lane, Kharkov, 61103, Ukraine,  
Tel. +38 (057) 717-5555

## Atomic Metal Conditioner Maximum Diesel Truck for diesel engine



*Atomic Metal Conditioner Maximum Diesel Truck for diesel engine with 1 Stage Revitalizant is an innovative product specially designed for diesel engines of heavy-duty vehicles with oil capacity system up to 30-45 L. Due to Revitalizant the product reduces friction, rebuilds worn metal in engine parts and creates protective coating against future wear, thus providing tools-free restoration and anti-wear protection. Product application prolongs the life of your engine and allows avoiding expensive repairs in the future. One treatment lasts for 100,000 km!*

### Benefits:

- ❖ Restores parts' surfaces and compensates current wear;
- ❖ Levels and increases compression in cylinders;
- ❖ Increases pressure in oil system up to the nominal level;
- ❖ Creates active protection system for parts against overloading and overheating;
- ❖ Reduces noise and vibration level;
- ❖ Improves oil lubricating properties and tribological characteristics of engine assemblies;
- ❖ Increases service life of an engine;
- ❖ Reduces fuel consumption;
- ❖ Increases engine power and acceleration capability;
- ❖ One treatment lasts for 100,000 km of run.

### Application:

The temperature of the compound before application should not be lower than +25°C.

Shake the bottle. Apply the compound into the oil filler neck of the engine, warmed up to the operating temperature.

Start the engine and provide its idle operation for 3-5 minutes.

### Dosage:

1 bottle (950 ml) is enough for the engine with an oil capacity system with 30-45 L volume. Oil level should not exceed the maximal level of oil gage. Avoid over dosage.

### Note:

- ❖ Specially designed for diesel engines with turbocharging which operate under high loaded modes (SHPD – Super High Performance Diesel, UHPD – Ultra High Performance Diesel). Compatible with all types of motor oils. Revitalization takes place during 1000-1500 km. It is not recommended to change oil during this period.
- ❖ Granules of atomic revitalizant are completely dissolved in motor oil under operating temperature.
- ❖ For the highest level of protection for your vehicle's engine use XADO Atomic Oil in the future.

**XADO**

SMART NANOTECHNOLOGY FOR YOUR CAR

XADO Technology Ltd. Headquarters: 4, 23 Augusta Lane, Kharkov, 61103, Ukraine,  
Tel. +38 (057) 717-5555

### Technical Information:

Parameter name*	Standard according to product acceptance standard	Actual data
1. Appearance	Red colour clear liquid	Red colour clear liquid
2. Kinematic viscosity mm <sup>2</sup> /s at 40 °C, not less than	9.0	149.5
3. Water content, not more than	Traces	Traces
4. Flash point in the open crucible, not lower than	62	145
5. Corrodibility on the plates of lead motor oil according to GOST 10541 with 3 % wt. conditioner	Absence of corrodibility	Absence of corrodibility
6. Density at 20°C, g/cm <sup>3</sup> , not less than	0.808	1.169
* - The tests on all parameters are performed with preliminary mixing of the sample		

### Package:

Art. XA 40712 (Bottle 950 ml)